

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name Newport Gas Refill
Container size 90ml, 250ml, 300ml, 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses To be used for refilling butane-powered domestic products
Uses advised against Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier Keen-Newport Group Limited
Unit 31 Kingfisher Court
Newbury
Berkshire
RG14 5SJ

1.4. Emergency telephone number

Emergency telephone +44 (0)1635 34600 (Mon-Fri 09:00-17:00)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification (EC 1272/2008)**

Physical hazards Aerosol 1 - H222, H229
Health hazards Not Classified
Environmental hazards Not Classified

2.2. Label elements**Pictogram**

Signal word Danger
Hazard statements H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P102 Keep out of reach of children.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

butane CAS number: 106-97-8 EC number: 203-448-7 REACH registration number: 01-2119474691-32-XXXX Contains no other substances or impurities which will influence the classification of the product.			30-60%
Classification Flam. Gas 1 - H220 Press. Gas (Liq.) - H280		Classification (67/548/EEC or 1999/45/EC) F+; R12. Extremely flammable.	
isobutane CAS number: 75-28-5 EC number: 200-857-2 REACH registration number: 01-2119485395-27-0000 Contains no other substances or impurities which will influence the classification of the product.			10-30%
Classification Flam. Gas 1 - H220 Press. Gas (Liq.) - H280		Classification (67/548/EEC or 1999/45/EC) F+; R12. Extremely flammable.	
propane CAS number: 74-98-6 EC number: 200-827-9 REACH registration number: 01-2113486944-21-0000 Contains no other substances or impurities which will influence the classification of the product.			10-30%
Classification Flam. Gas 1 - H220 Press. Gas (Liq.) - H280		Classification (67/548/EEC or 1999/45/EC) F+; R12. Extremely flammable.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information	`If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin contact	Rinse with water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May be slightly irritating to eyes. May cause discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Vapours may form explosive mixtures with air.

Hazardous combustion Products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during Firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Usage precautions Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection**8.1. Control parameters****Occupational exposure limits****butane**

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

isobutane

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

800ppm (TWA/TLV)

propane

TLV (ACGHIH) - 1.000 ppm

WEL = Workplace Exposure Limit

8.2. Exposure controls**Appropriate engineering controls** Provide adequate ventilation.**Eye/face protection** Avoid contact with eyes. Large Spillages: Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.**Hand protection** No specific hand protection recommended.**Hygiene measures** Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.**Respiratory protection** No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.**Environmental exposure controls** Keep container tightly sealed when not in use. Avoid release to the environment.**SECTION 9: Physical and Chemical Properties****9.1. Information on basic physical and chemical properties**

Appearance	Aerosol.
Colour	Colourless.
Odour	Natural gas
pH	No information available.
Melting point	-11°C
Initial boiling point and range	No information available.
Flash point	No information available.
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	No information available
Vapour pressure	2.73 Bar @ 20°C
Vapour density	No information available.
Relative density	No information available.
Solubility(ies)	No information available.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

Viscosity	No information available.
Explosive properties	No information available.
Explosive under the Influence of a flame	Yes
Oxidising properties	Not available.

9.2. Other information

Other information	Gas/vapour heavier than air. May accumulate in confined spaces, particular at or below ground level.
-------------------	--

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reactivity	See the other subsections of this section for further details.
------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidising agents.
------------------------------------	--

10.4. Conditions to avoid

Conditions to avoid	Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated
---------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition Products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
----------------------------------	--

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity - oral**

Notes (oral LD ₅₀)	Based on available data the classification criteria are not met.
--------------------------------	--

Acute toxicity - dermal

Notes (dermal LD ₅₀)	Based on available data the classification criteria are not met.
----------------------------------	--

Acute toxicity - inhalation

Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
--------------------------------------	--

Skin corrosion/irritation

Animal data	Based on available data the classification criteria are not met.
-------------	--

Serious eye damage/irritation

Serious eye damage/irritation	Based on available data the classification criteria are not met.
-------------------------------	--

Respiratory sensitisation

Respiratory sensitisation	Based on available data the classification criteria are not met.
---------------------------	--

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

Skin sensitisation**Skin sensitisation** Based on available data the classification criteria are not met.**Germ cell mutagenicity****Genotoxicity - in vitro** Based on available data the classification criteria are not met.**Carcinogenicity****Carcinogenicity**

Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.**Reproductive toxicity - development**

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.**Specific target organ toxicity - repeated exposure****STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.**Aspiration hazard****Aspiration hazard** Based on available data the classification criteria are not met.**General information**

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Spray/mists may cause respiratory tract irritation.

Ingestion

Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Eye contact

May be slightly irritating to eyes. May cause discomfort.

Route of exposure

Ingestion Inhalation Skin and/or eye contact

Target organs

No specific target organs known.

Toxicological information on ingredients.**butane****Acute toxicity - oral****Notes (oral LD₅₀)** Technically not feasible.**Acute toxicity - dermal****Notes (dermal LD₅₀)** Technically not feasible.**Acute toxicity - inhalation****Acute toxicity inhalation (LC₅₀ vapours mg/l)** 1,443.0**Species**

Rat

ATE inhalation (vapours mg/l) 1,443.0

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

Skin corrosion/irritation
Skin corrosion/irritation Technically not feasible.

Serious eye damage/irritation
Serious eye damage/irritation Technically not feasible.

Respiratory sensitisation
Respiratory sensitisation Data lacking

Skin sensitisation
Skin sensitisation Technically not feasible.

Germ cell mutagenicity
Genotoxicity - in vitro Negative.
Genotoxicity - in vivo Negative.

Carcinogenicity
Carcinogenicity Data lacking.

isobutane

Acute toxicity - oral
Notes (oral LD₅₀) Technically not feasible.

Acute toxicity - dermal
Notes (dermal LD₅₀) Technically not feasible.

Acute toxicity - inhalation
Acute toxicity inhalation
(LC₅₀ gases ppmV) 800,000.0

Species Rat

ATE inhalation (gases ppm) 800,000.0

Skin corrosion/irritation
Skin corrosion/irritation Technically not feasible.

Serious eye damage/irritation
Serious eye damage/irritation Technically not feasible.

Respiratory sensitisation
Respiratory sensitisation Data lacking.

Skin sensitisation
Skin sensitisation Technically not feasible.

Germ cell mutagenicity
Genotoxicity - in vitro Negative.
Genotoxicity - in vivo Negative.

Carcinogenicity
Carcinogenicity There is no evidence that the product can cause cancer.

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

Specific target organ toxicity - single exposure

STOT - single exposure Not classified

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified

Inhalation Irregular cardiac activity.

propane**Acute toxicity - oral**Notes (oral LD₅₀) Technically not feasible.**Acute toxicity - dermal**Notes (dermal LD₅₀) Technically not feasible.**Acute toxicity - inhalation**Acute toxicity inhalation
(LC₅₀ vapours mg/l) 1,443.0**Species**

Rat

ATE inhalation (vapours mg/l) 1,443.0

Skin corrosion/irritation

Skin corrosion/irritation Technically not feasible.

Serious eye damage/irritation

Serious eye damage/irritation Technically not feasible.

Respiratory sensitisation

Respiratory sensitisation Data lacking.

Skin sensitisation

Skin sensitisation Technically not feasible.

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Genotoxicity - in vivo Negative.

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

Reproductive toxicity

Reproductive toxicity – fertility Screening - NOAEC 3.000 ppm, Inhalation, Rat

Reproductive toxicity – development Developmental toxicity: - NOAEC: 9.000 ppm, Inhalation,

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

hazardous effects on the environment.

12.1. Toxicity**Toxicity** Based on available data the classification criteria are not met.

Ecological information on ingredients.

Butane**Acute aquatic toxicity**

Acute toxicity - fish	LC ₅₀ , 96 hours: 49.9 mg/l, Fish
Acute toxicity - aquatic Invertebrates	LC ₅₀ , 48 hours: 69.43 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 19.37 mg/l, Algae

Isobutene**Toxicity** The product is not believed to present a hazard due to its physical nature.**Acute aquatic toxicity**

Acute toxicity - fish	LC ₅₀ , 96 hours: 49.9 mg/l, Fish
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: 69.43 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 19.37 mg/l, Algae

Propane**Acute aquatic toxicity**

Acute toxicity - fish	LC ₅₀ , 96 hours: 49.9 mg/l, Fish
Acute toxicity - aquatic Invertebrates	LC ₅₀ , 48 hours: 69.43 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 19.37 mg/l, Algae

12.2. Persistence and degradability**Persistence and degradability** The degradability of the product is not known.

Ecological information on ingredients.

Butane

Phototransformation	Air - DT ₅₀ : 1906 days
Biodegradation	Water - Degradation 100: 385.5 hours

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

Isobutene**Persistence and degradability
Biodegradation**

Not applicable.
Water - Half-life 100: 6,9 days

Propane**Phototransformation
Biodegradation**

Air - DT₅₀ : 1906 days
Water - Degradation 100: 385.5 hours

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.**butane****Bioaccumulative potential
Partition coefficient**

The product does not contain any substances expected to be bioaccumulating.
log Pow: 2,89

isobutane**Bioaccumulative potential
Partition coefficient**

Because of the low log kow, accumulation in organisms is not to be expected.
log Pow: ~ 2,76

propane**Bioaccumulative potential
Partition coefficient**

Because of the low log kow, accumulation in organisms is not to be expected.
log Pow: ~ 3

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Ecological information on ingredients.**butane****Mobility**

No data.

isobutane**Mobility**

No data.

propane**Mobility**

No data.

12.5. Results of PBT and vPvB assessment**Ecological information on ingredients.****butane****Results of PBT and vPvB**

This product does not contain any substances classified as PBT or vPvB.

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

assessment**Results of PBT and vPvB
assessment****isobutane**

This product does not contain any substances classified as PBT or vPvB.

**Results of PBT and vPvB
assessment****propane**

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects**Other adverse effects** None known.**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information**14.1. UN number****UN No. (ADR/RID)** 1950**UN No. (IMDG)** 1950**UN No. (ICAO)** 1950**UN No. (ADN)** 1950**14.2. UN proper shipping name****Proper shipping name (ADR/RID)** AEROSOLS**Proper shipping name (IMDG)** AEROSOLS**Proper shipping name (ICAO)** AEROSOLS**Proper shipping name (ADN)** AEROSOLS**14.3. Transport hazard class(es)****ADR/RID class** 2.1**ADR/RID classification code** 5F**ADR/RID label** 2.1**IMDG class** 2.1

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

ICAO class/division 2.1

ADN class 2.1

Transport labels**14.4. Packing group****14.5. Environmental hazards****Environmentally hazardous substance/marine pollutant**

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

Health and Safety at Work etc. Act 1974 (as amended).
 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
 EH40/2005 Workplace exposure limits.
 The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
 Commission Regulation (EU) No 2015/830 of 28 May 2015.
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
 Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories**EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

SECTION 16: Other information**Abbreviations and acronyms used in the safety data sheet**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
 RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

IATA: International Air Transport Association.
ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
IMDG: International Maritime Dangerous Goods.
CAS: Chemical Abstracts Service.
ATE: Acute Toxicity Estimate.
LC₅₀: Lethal Concentration to 50 % of a test population.
LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
EC₅₀: 50% of maximal Effective Concentration.
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.

**Classification abbreviations
and acronyms**

Aerosol = Aerosol

**Classification procedures
according to Regulation (EC)
1272/2008**

Aerosol 1 - H222, H229: : Expert judgement.

Training advice

Read and follow manufacturer's recommendations.

Revision date

08/03/2018

Revision

1

SDS number

4856

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H280 Contains gas under pressure; may explode if heated.

Issue date: 01.01.2025

Newport Butane Refill

Manufactured in the UK

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.